




HIGH PERFORMANCE MONOCRYSTALLINE PERC MODULE



RISEN ENERGY CO., LTD.

Risen Energy is a leading, global tier 1 manufacturer of high-performance solar photovoltaic products and provider of total business solutions for residential, commercial and utility-scale power generation. The company, founded in 1986, and publicly listed in 2010, compels value generation for its chosen global customers. Techno-commercial innovation, underpinned by consummate quality and support, encircle Risen Energy's total Solar PV business solutions which are among the most powerful and cost-effective in the industry. With local market presence and strong financial bankability status, we are committed, and able, to building strategic, mutually beneficial collaborations with our partners, as together we capitalise on the rising value of green energy.



Preliminary
For Global Market

RSM150-8-485M-510M

150 CELL

Mono PERC Module

485-510Wp

Power Output Range

1500VDC

Maximum System Voltage

20.8%

Maximum Efficiency

KEY SALIENT FEATURES



Global, Tier 1 bankable brand, with independently certified state-of-the-art automated manufacturing



Industry leading lowest thermal co-efficient of power



Industry leading 12 years product warranty



Excellent low irradiance performance



Excellent PID resistance



Positive tight power tolerance



Dual stage 100% EL Inspection warranting defect-free product



Module Imp binning radically reduces string mismatch losses



Warranted reliability and stringent quality assurances well beyond certified requirements




Certified to withstand severe environmental conditions

- Anti-reflective & anti-soiling surface minimise power loss from dirt and dust
- Severe salt mist, ammonia & blown sand resistance, for seaside, farm and desert environments
- Excellent mechanical load 2400Pa & snow load 5400Pa resistance

LINEAR PERFORMANCE WARRANTY


12 year Product Warranty / 25 year Linear Power Warranty



★ Please check the valid version of Limited Product Warranty which is officially released by Risen Energy Co., Ltd

Dimensions of PV Module

Unit: mm



ELECTRICAL DATA (STC)

Model Number	RSM150-8-485M	RSM150-8-490M	RSM150-8-495M	RSM150-8-500M	RSM150-8-505M	RSM150-8-510M
Rated Power in Watts-Pmax(Wp)	485	490	495	500	505	510
Open Circuit Voltage-Voc(V)	50.35	50.57	50.79	51.01	51.23	51.45
Short Circuit Current-Isc(A)	12.25	12.32	12.39	12.46	12.53	12.60
Maximum Power Voltage-Vmpp(V)	42.22	42.44	42.66	42.88	43.10	43.32
Maximum Power Current-Imp(A)	11.50	11.56	11.62	11.68	11.74	11.80
Module Efficiency (%) *	19.8	20.0	20.2	20.4	20.6	20.8

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

* Module Efficiency (%): Round-off to the nearest number

ELECTRICAL DATA (NMOT)

Model Number	RSM150-8-485M	RSM150-8-490M	RSM150-8-495M	RSM150-8-500M	RSM150-8-505M	RSM150-8-510M
Maximum Power-Pmax (Wp)	367.7	371.5	375.4	379.3	383.2	387.1
Open Circuit Voltage-Voc (V)	46.83	47.03	47.23	47.44	47.64	47.85
Short Circuit Current-Isc (A)	10.05	10.10	10.16	10.22	10.27	10.33
Maximum Power Voltage-Vmpp (V)	39.18	39.38	39.59	39.79	40.00	40.20
Maximum Power Current-Imp (A)	9.38	9.43	9.48	9.53	9.58	9.63

NMOT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar cells	Monocrystalline
Cell configuration	150 cells (5×15×5×15)
Module dimensions	2220×1102×40mm
Weight	28kg
Superstrate	High Transmission, Low Iron, Tempered ARC Glass
Substrate	White Back-sheet
Frame	Anodized Aluminium Alloy type 6005-2T6, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm ² (12AWG), Positive(+) 270mm, Negative(-) 270mm
Connector	Risen Twinsel PV-SY02, IP68

TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	44°C±2°C
Temperature Coefficient of Voc	-0.28%/°C
Temperature Coefficient of Isc	0.05%/°C
Temperature Coefficient of Pmax	-0.36%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	20A
Limiting Reverse Current	20A



PACKAGING CONFIGURATION

	40ft(HQ)	20ft
Number of modules per container	540	270
Number of modules per pallet	27	27
Number of pallets per container	20	10
Packaging box dimensions (LxWxH) in mm	2250×1130×1235	2250×1130×1235
Box gross weight[kg]	810	810

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

©2020 Risen Energy. All rights reserved. Specifications included in this datasheet are subject to change without notice.

THE POWER OF RISING VALUE



Our Partners: